



Safety air gun with entirely unique advantages

SILVENT 007-L Met een lavale nozzel is algemeen het meest gekozen alternatief. Een roestvrij stalen lavale mond gemonteerd op het 007-handvat kan bijna elke blaasfunctie aan. Een lavale opening in het midden van de blaasmond creëert een sterk geconcentreerde luchtstroom die zich aan supersonische snelheid voortbeweegt. Rond de lavale opening zijn een aantal gleuven en groeven, die een krachtige, stille en laminaire luchtstroom voortbrengen. Deze combinatie voorziet een superieure reinigingsprestatie en optimaal gebruik van de perslucht, samen gebracht in dit blaaspistool. Vinnen voorkomen direct contact tussen de huid en de uitblazende openingen.

Voldoet volledig aan de OSHA-veiligheidsnormen en de EU Machine Directive geluidsbepalingen. Gepatenteerd.

Order no: **007-L**

| | | |
|---------------------------|-----------------------|-------------|
| Replace open pipe Ø | 4 mm | (5/32") |
| Booster position: | | |
| Blowing force | 3.5 N | (12.4 oz) |
| Air consumption | 22 Nm ³ /h | (12.9 scfm) |
| Sound level | 82 dB(A) | |
| Variable position: | | |
| Blowing force | 1.6 N | (5.6 oz) |
| Air consumption | 11 Nm ³ /h | (6.5 scfm) |
| Sound level | 75 dB(A) | |
| Blowing pattern | Laval | |
| Connection | G 1/4" | 1/4"-18 NPT |
| Nozzle | 1001 | |
| Material (nozzle) | Stainless steel | |

1 TWO-STEP SYSTEM The 007 grip features a unique valve design with a two-step system that considerably reduces both noise levels and energy consumption. The first step, variable position, allows variable adjustment of the blowing force and is more than adequate for most types of work. It generates a low sound level and permits energy savings of up to 50%. The gun's second step, the "booster position", delivers twice the blowing force for the most demanding operation.

2 TOP & BOTTOM CONNECTION

The grip offers two connection possibilities – both top and bottom air supply connection. From the viewpoint of safety, as well as ergonomics, top connection is the best alternative. Safety valves at the connections eliminate the risk of injury.

3 SOFTGRIP HANDLE The 007 safety gun has an ergonomically designed Softgrip handle of synthetic rubber that is highly durable and oil resistant. The material insulates well against heat and cold, and the handle is easy on the hand and wrist.

Noise reduction

60%

Air/cost savings

27%

Extension pipes in 6 lengths

standard - 100 mm (4")



Our 007 safety air gun series is available with six different extension pipe lengths. The pipes are made of galvanized steel. When ordering safety guns with extension pipes that are longer than 100 mm (4"), specify the pipe length last in the order number. Safety gun-extension pipe length: e.g. **007-L-1000**.

ALTERNATIVES



Order no: **007-S**



Order no: **007-Z**

ACCESSORIES



Order no: **590**



Order no: **AS1**

Perslucht is niet ongevaarlijk. Hoge drukken welke in contact komen met de huid kunnen serieuze letsels veroorzaken. De OSHA norm is hiervoor ingesteld. Het grote voordeel is dat er nooit meer dan 2 bar direct in contact kan komen met de huid en door de speciale nozzle heeft u een significante vermindering in het aantal vrijgekomen decibellen.

